

**WATERPUMP SPECIFICATIONS**

|                      |        |        |
|----------------------|--------|--------|
| Inlet/outlet thread  | Inches | 4"     |
| Max. flow            | l/h    | 90.000 |
| Maximum suction head | m      | 5      |
| Total head           | m      | 30     |
| Noise level          | dB(A)  | 104    |

**ENGINE SPECIFICATIONS**

|                     |         |        |
|---------------------|---------|--------|
| Engine manufacturer | Robin   |        |
| Model               | EX40    |        |
| Fuel                | Essence |        |
| Cycles              | 4 temps |        |
| Displacement        | cc      | 404    |
| Maximum power       | hp      | 14     |
| N°. of cylinders    |         | 1      |
| Startingsystem      |         | Recoil |
| Fuel tank capacity  | L       | 3,6    |

**PUMP SPECIFICATIONS**

|                  |                 |
|------------------|-----------------|
| Brand            | Benza           |
| Type             | Centrifugal     |
| Mechanical seal  | Silicon carbide |
| Self-priming     | Yes             |
| Suitable for     | Clear waters    |
| Debris Maximum Ø | mm              |
|                  | 7,5             |

**STANDARD ACCESORIES**

Strainer, connecting pieces and clamps

**DIMENSIONS & WEIGHT**

|        |    |     |
|--------|----|-----|
| Length | mm | 820 |
| Width  | mm | 705 |
| Height | mm | 640 |
| Weight | kg | 76  |


**DÉBIT**

**Ø ENTRÉE  
/SORTIE**

**ESSENCE**

**DÉMARRAGE  
MANUEL**
