



## High Volume Bow and Rocker

With a raised bow height the X-Sled is able to handle tethers in swift water whilst reducing the risk of the bow diving when loaded. The increased volume maintains stability when occupied by a casualty or rescuer.

## Inflation and overpressure valves

Leafield valves are used and are widely recognised as world leaders in valve manufacturing. Our valves all work with our boat inflation kit and pump.

## Low profile grab handles

Fitted with 15 low profile grab handles, aiding team carries and in-water casualty management.

## 15 cm Airdeck hull

The new 15 cm PVC Fusion Dropstitch offers high floatation, dry deck and a rigid platform.

## 3 Chambers

The sled is built with 3 separate inflatable chambers, providing added security should one of the chambers become compromised.

## 3 Person craft

The X-Sled has been designed to carry 2 rescuers and 1 casualty. Although the sled will float up to 5 people successfully, this does affect its use in turbulent water.



## TECHNICAL PROPERTIES

MATERIAL	PVC with Fusion Dropstitch
FLOOR THICKNESS	15 cm
TUBE WIDTH	24,5 cm
AIR CHAMBERS	3 compartments
BOW RISE	56 cm
D-RINGS	5, stainless steel 316
REFLECTIVE STRIPES	8
HANDLES	15
PROPELLION	Connector split paddle (not included), Tow
INFLATION	Pump or inflation kit (not included)
PRESSURE	Tubes 3,6 PSI & Floor 9 PSI
BAG	Included
VALVES	Leafield C7/D7 + A6 pressure relief valves on each chamber
WARRANTY	3 years
CAPACITY	350 kg or 3 persons (swift water) Floats up to 5 persons (flat water)